

IN THE DRAWINGS

Please replace the previously filed informal drawing sheet with the attached replacement sheet.

REMARKS


The above-noted amending of claim 1 and addition of claims 2-11, 1 replacement formal drawing sheet, as well as the submission of a substitute Specification (marked copy and clean copy), are respectfully submitted in order to more clearly and appropriately claim the subject matter which application considers to constitute his inventive contribution. In addition, the amendments to the Specification are submitted in order to clarify and correct the Specification and to conform it to all of the requirements of U.S. practice.

In view of the foregoing remarks, the application is believed to be in condition for allowance, and early notice to this effect is earnestly solicited. If allowance of this application may be expedited by resolution of simple issues through a telephone conference, the Examiner is welcome to call the undersigned.

If there are any additional charges in connection with this requested amendment, the Examiner is authorized

Dated: January 28, 2004

Respectfully submitted,

By 
Scott S. Servilla
Registration No.: 40,806
LERNER, DAVID, LITTENBERG,
KRUMHOLZ & MENTLIK, LLP
600 South Avenue West
Westfield, New Jersey 07090
(908) 654-5000
Attorney for Applicant

E-Z PATCH PATCH SYSTEM AND METHODFIELD OF THE INVENTION

[0001] E-Z Patch was invented to solve a common problem in the construction, plumbing, electrical, sheetrock and any type of home, personal, office or business use. This invention relates to a patch for walls, ceilings and floors and a method for patching walls, ceilings and floors.

BACKGROUND OF THE INVENTION

[0002] The idea was first thought up when the common problem occurred on how to quickly and effectively repair a hole or damaged area in the home or office, in the wall, ceiling or even possibly the floor. E-Z Patch itself comes in a variety of sizes; with each size also have the capabilities of being able to be easily modified and or trimmed to fit each hole precisely. E-Z Patch is easily applied to the damaged area using the self-adhesive backing. Its advantage, not only in labor and time saved, but allowing the average homeowner to easily make the necessary repair! A common problem is the need to quickly and effectively repair a hole or damaged area in a wall, ceiling or a floor of a building such as a home, office or other structure. Existing methods are labor-intensive and expensive.

[0003] The drawing shows various views including: isometric, plan and elevation view. The drawing only represents but only 1 size E-Z Patch. Sizes available will be from 1/2" up to and including 6". It would be advantageous to provide a patch system and methods for patching holes in walls, ceiling or floors that require less labor and materials than presently existing methods.

SUMMARY OF THE INVENTION

[0004] According to one or more embodiments of the invention, a patch system is provided that includes a plug material including an adhesive backing. According to certain embodiments, a method of patching a hole is provided comprising at least selecting a patch system including a plug material and an adhesive backing, inserting the plug into the hole and applying the adhesive backing to the area surrounding the hole.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] A more complete appreciation of the subject matter of the present invention and the various advantages thereof can be realized by reference to the following detailed description in which reference is made to the accompanying drawings.

[0006] Figure 1 is a perspective view of a patch system according to one embodiment of the present invention;

[0010] Figure 2 a top plan view of the patch system shown in Figure 1; and

[0011] Figure 3 is a side view of the patch system shown in Figure 1.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0012] One or more embodiments of the present invention provide a patch system and method for patching holes in ceilings, walls and floors. Turning now to the drawings and particularly to Figures 1-3, a patch system is shown generally by reference numeral 10. The patch system 10 includes a plug material 12 adapted to be placed in a hole and an adhesive backing 14 in contact with the plug 12 such that the adhesive backing surrounds the periphery of the hole. It will be understood that the plug material 12 can be made of any suitable material, but preferably, the plug 12 is made from a lightweight foam material such as Styrofoam®. According to certain preferred embodiments, the plug material 12 is fireproof. The plug material 12 is pre-molded, and the plug 12 can be sized in depth and shape to fit various sized holes. The adhesive backing 14 preferably includes a flexible material such paper with an adhesive backing or Mylar® film.

[0013] One or more embodiments of the invention solves a common problem in the construction and maintenance of buildings such as homes and offices. Given the simplicity and ease of use individuals in the plumbing, electrical, sheetrock trades

as well as individuals can use the patch system according to the present invention.

[0014] As noted above, the patch system can be supplied in a variety of sizes. Examples of available sizes are from 1/2" up to and including 6". Each size also is made in a manner such that the patch system be easily modified and or trimmed to precisely fit in different sized holes. Thus, each size is capable of being easily modified if necessary to fit the repaired hole precisely and quickly. According to one or more embodiments, the patch system can be easily applied to a damaged area using the self-adhesive backing. The patch system and method according to the present invention saves labor and time and also but allows the average homeowner to easily make the necessary repair.

[0015] The patch system according to one or more embodiments fills the need for a fast, quick, easy and permanent repair to any wall, ceiling and or flooring surface. In use, one would simply find the correctly sized patch for the hole that has to be repaired, peel the backing off the self adhesive material, and simply insert the plug in the center of the adhesive patch into the hole to be repaired. The self-adhesive backing attaches firmly to the surface surrounding the patched hole. The patch job can then be finished as necessary using spackling or finishing whatever material is desired for the particular surface. The patch system of the present invention is easily applied to the damaged area using the self-adhesive backing.

[0016] The patch system of the present invention has a self adhesive backing for easy use and a lightweight foam plug such as a Styrofoam® plug in the center that can be easily shaped to precisely fit the damaged hole precisely. The present invention substantially reduces the time and labor required to

patch holes in walls, ceilings and floors without having to replace the damaged area. Thus, according to one or more embodiments of the present invention a substantially one step repair patch system and method are provided. The plug material provides is strength and support to the repaired area. The patch system and method can be used for any repair in all types of construction/carpentry, including but not limited to any wall, ceiling and or floor.

[0017] Although the invention herein has been described with reference to particular embodiments, it is to be understood that these embodiments are merely illustrative of the principles and applications of the present invention. It is therefore to be understood that numerous modifications may be made to the illustrative embodiments and that other arrangements may be devised without departing from the spirit and scope of the present invention as defined by the appended claims and their equivalents.